

# QUICK-STEP® PARQUET PRODUCT DATA

## ITEM

	<b>Total Thickness</b>		14.00mm
	<b>Dimensions</b>	Quick-Step® Imperio	220mm x 2200mm (Planks)
		Quick-Step® Palazzo	190mm x 1820mm (Planks)
		Quick-Step® Variano	190mm x 2200mm (Planks)
	<b>Packaging</b>	Quick-Step® Imperio	4 planks/pack (1.9360m <sup>2</sup> )
		Quick-Step® Palazzo	6 planks/pack (2.0748m <sup>2</sup> )
		Quick-Step® Variano	6 planks/pack (2.5080m <sup>2</sup> )
	<b>Total Weight</b>	Quick-Step® Imperio	10.12kg/m <sup>2</sup>
		Quick-Step® Palazzo	9.39kg/m <sup>2</sup>
		Quick-Step® Variano	10.11kg/m <sup>2</sup>
	<b>Colour Range</b>		8 Selected Colours
	<b>Tongue and Groove</b>		Uniclic® Multifit for Parquet
	<b>CE Conformity</b>		DAP-PL-1033.00 Level 4
	<b>Sustainability of Forest</b>	PEFC label	
	<b>Wear Resistance/ Class</b>	Quick-Step® Imperio / Palazzo:	SIS 923509 - Falling Sand 500-1700 DIN 68861 - S33 550-1200
		Quick-Step® Variano:	SIS 923509 - Falling Sand 800-1000 DIN 68861 - S33 100-1050
			* Anti-scratch Top Coat with nano-technology.
	<b>General Aspects of Installed Floor</b>	EN 13489	
	<b>Stain Resistance</b>	EN 13442	All except blue ink Class 5 Blue ink Class 3
	<b>Castor Wheel Test</b>	EN 12529	Use soft castors or office mat
	<b>Slip Resistance</b>	CEN/TS 15676	USRV 50-52
	<b>Formaldehyde Emission</b>	EN 717-1	E1
	<b>Thermal Resistance</b>	EN 12664	0.127 m <sup>2</sup> . °K/W
	<b>Underfloor Heating</b>		Consult special installation instructions
	<b>Reaction to Fire</b>	EN 14342	CWFT Dfl-S1 With Oak Top Layer Cfl-S1
	<b>Panel Construction</b>	Surface layer Coreboard:	PEDC, FSC 3.00mm Hevea - QS Mastercore
		Backing Layer:	PEDC, FSC 2.00mm
	<b>Surface Layer</b>	EN 14342:2008	Oak
	<b>Finishing</b>	Quick-Step® Imperio	UV-curving varnish: 7 Layers UV-curving oil: 2 Layers
		Quick-Step® Palazzo	UV-curving varnish: 5-7 Layers UV-curving oil: 2 Layers
		Quick-Step® Variano	UV-curving oil: 2 Layers

It is advised to confirm stock availability on 0861-833-338.